

# Construction Air Tools – Hand Drill

## Hand Drill – VK 14RR (15 lb)



### Features

- Spring retainer
- “D” handle with outside trigger
- Teasing throttle for precise control
- Muffler available to reduce noise
- Right-hand rotation

**VK-14RR Rotary Hammers** technically equivalent to CP 14RR Hand Drill are designed for a wide variety of construction and maintenance applications such as driving or setting masonry anchors and drilling holes in concrete, bricks or rock. As a hammer, these tools can be used for chipping, scarifying, scaling and cleaning welds.

### Applications

- Bolting applications - such as Raw bolts and foundation bolting
- Quarry pop shots
- Plugging
- Demolition shots and sign-hanging
- Drilling in concrete, granite, limestone, brick work

### Technical Data

Model – VK 14RR		
Specifications	Metric	Imperial
Weight	6.5 kg	14.3 lb
Length	480 mm	19"
Blow per Minute	2520	2520
Piston Stroke	35 mm	1.38"
Air Inlet	9.5 mm	3/8"
Air Pressure	6 bar	87 psi
Air Consumption	22 l/s	47 cfm
Retainer Type	Spring	Spring
Shank Size	22 × 82.5 mm	7/8" X 3 1/4"

  

Model with Silencer - VK 14RRS		
Weight with Silencer	7 kg	15.4 lb

