

# Construction Air Tools – Paving Breaker

## Paving Breaker – VK 1230 ( 64 lb )

The **VK 1230 ( 64 lb )** series of demolition tools technically equivalent to CP 1230 Paving Breaker are engineered to provide the strength and resilience required for a wide range of demanding construction and plant maintenance tasks. These include breaking reinforced concrete, tackling heavy road works, cutting through tarmac, working with frozen ground, handling non-consolidated rock, and performing general demolition duties.

The standard tools are available either in a basic version, a version with a muffler and versions with extra vibration dampening (SVR models). The mufflers can also be bought separately for retro-fitting. All breakers are available with a choice of different shanks, to accommodate needs from different markets and customers

### Technical Data

Model – VK 1230 Paving Breaker		
Specifications	Metric	Imperial
Weight	29 kg	64 lb
Length	680 mm	27"
Blow per Minute	1300	1300
Piston Dia	60.3 mm	2.40"
Piston Stroke	140 mm	5.50"
Air Inlet	19 mm	¾"
Air Pressure	6 bar	87 psi
Air Consumption	30 l/s	64 cfm
Shank Size	32 x 160 mm	1¼" x 6¼"
Shank Size (optional)	28 x 160 mm	1⅛" x 6¼"
Model With Silencer – VK 1230S		
Weight With Silencer	30 kg	66 lb

### Features

- Alloy steel forgings for excellent durability
- Four-bolt back head withstands rugged use
- Integral oiler provides continuous lubrication
- Reversible piston reduces maintenance cost
- Air inlet swivel for easy manoeuvrability

