

Construction Air Tools – Chipping hammer

CHIPPING HAMMER – VK 4130 (20 LB)

VK 4130 Chipping Hammer technically equivalent to CP 4130 comes with “D” Handle outside trigger Four Bolt locking system gives higher airflow and easy to handle. It is particularly suitable for working with relatively hard concrete in demolition, pile-capping or bridge deck applications, foundries, fabrication shops and construction applications .This chipping hammer comes with 2,3,4 cylinder option along with round & hex bush options.

Features

- Four bolt, high strength back-head
- “D” handle with outside trigger and extra safety mechanism
- Simplate valve for smooth operation
- Strong and reliable
- Available in 3” or 4” cylinder stroke versions (4130)
- Choice of Bushing Round or Hex

Technical Data

Model – VK 4130 Chipping Hammer		
Specifications	Metric	Imperial
Weight	9 kg	20 lb
Length	387 mm	15.25"
Air Consumption	15.5 l/s	33 cfm
Blows per minute	2280	2280
Piston Stroke	76.2 mm	3"
Air Pressure	6.2 bar	90 psi
Piston Dia	28.6 mm	1.13"
Air Inlet (UNS thread)	22.2 mm	7/8"
Retainer Type	Spring	Spring
Shank Hex	14.7 mm	0.580"
Shank Round	17.3 mm	0.680"

