

Construction Air Tools – Paving Breaker

Paving Breaker – VK 1240 (86 lb)

The **VK 1240 (86 lb)** series of demolition tools technically equivalent to CP 1240 Paving Breaker are engineered to provide the strength and resilience required for a wide range of demanding construction and plant maintenance tasks. These include breaking reinforced concrete, tackling heavy road works, cutting through tarmac, working with frozen ground, handling non-consolidated rock, and performing general demolition duties.

The standard tools are available either in a basic version, a version with a muffler and versions with extra vibration dampening (SVR models). The mufflers can also be bought separately for retro-fitting. All breakers are available with a choice of different shanks, to accommodate needs from different markets and customers.

Technical Data

Model – VK 1240 Paving Breaker		
Specifications	Metric	Imperial
Weight	39 kg	86 lb
Length	735 mm	29.4"
Blow per Minute	1150	1150
Piston Dia	67 mm	2.63"
Piston Stroke	158 mm	6.25"
Air Inlet	19 mm	¾"
Air Pressure	6 bar	87 psi
Air Consumption	38 l/s	81 cfm
Shank Size	32 x 160 mm	1¼" x 6¼"
Shank Size (optional)	28 x 160 mm	1⅛" x 6¼"
Model With Silencer – VK 1240S		
Weight With Silencer	40 kg	88 lb

Features

- Alloy steel forgings for excellent durability
- Four-bolt back head withstands rugged use
- Integral oiler provides continuous lubrication
- Reversible piston reduces maintenance cost
- Air inlet swivel for easy manoeuvrability

